

ESD Diodes & Arrays



Indicates sorted columns
 * C_J TYP values indicated for this device
 ** Available only in -WN and -WR packing methods

Central Part Number <small>(Click to view product details)</small>	V _{RWM} MAX	ESD Voltage	C _J MAX	V _C MAX	Die Size (MILS)	Die Thickness (MILS)	Top Metallization (Å)	Bottom Metallization (Å)
CPZ35R-CMATVS3V3**	3.3V	30KV	45*	11V	10.2 X 10.2	3.9	AL (30000)	AU (9000)
CPZ35R-CMATVS3V3**	3.3V	30KV	45*	11V	10.2 X 10.2	3.9	AL (30000)	AU (12000)
CPZ34R-CTLTVS6V2**	4V	15KV	25*	10.7V	6.7 X 6.7	3.54	AL (30000)	AU (12000)
CPZ40R-CMO5V0LC**	5V	15KV	0.9	12V	13.4 X 13.4	3.9	AL (30000)	AU (9000)
CPZ40X-CMO5V0LC**	5V	15KV	0.9	12V	13.4 X 13.4	5.5	AL (30000)	AU (9000)
CPZ41X-CMKTVS5-4**	5V	15KV	3	14V	31.9 X 18.9	5.9	AL-SI (30000)	AU (15000)
CPZ39R-CMNTVS5V0**	5V	15KV	10	12.5V	11 X 11	3.94	AL (30000)	AU (9000)
CPZ36R-CMATVS5V0**	5V	30KV	40*	12.3V	10.2 X 10.2	3.9	AL (30000)	AU (12000)
CPZ33R-CMNTVS12V**	9V	8KV	10	18V	14.2 X 14.2	3.9	AL (13000)	AU (12000)
CPZ37R-CTLTVS12**	9V	30KV	14*	18V	6.7 X 6.7	3.54	AL (13000)	AU/AS-AG (13000/6000)